



Chicago Pneumatic CP781 Screwdrivers - Cushion 6.2-11.3NM

High torque & Robust. Reliable & easy-to-adjust cushion Clutch for powerful fastening. Robust Aluminum body & Steel clutch housing. Ideal tool for general assembly, metal, wood, PVC and refurbishing applications. Range: 6.2 - 11.3 Nm 4.57 - 8.4 ft.lbs

Specifications	Details
Actual air consumption	Metric: 7.6 l/s 453 l/mn Imperial: 16 cfm
Brand	Chicago Pneumatic
Length	Metric: 226 mm Imperial: 8.88"
Model Number	CP781
Output drive	1/4"
Height	Metric: 150 mm Imperial: 5.9"
Sound pressure	99.5 db(A)
Clutch type	Cushion
Min working torque	Metric: 6.2 Nm Imperial: 4.57 ft.lbs
Bit holder	Quick Change Hexagonal Female
Product Number	T025096
Sound Power	110.5 db(A)
Air inlet thread size	1/4"
Vibration ISO	ISO-28927-2
Average air consumption	Metric: 1.9 l/s 113 l/mn Imperial: 4 cfm
Max working torque	Metric: 11.3 Nm Imperial: 8.4 ft.lbs

Specifications	Details
Net weight	Metric: 1.36 kg Imperial: 3 lb
Free speed air consumption	Metric: 11.8 l/s Imperial: 25 cfm
Vibration uncertainty (K)	- m/s ²
Vibration	<2.5 m/s ²
Diameter	Metric: 31 mm Imperial: 0.78"
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Free Speed	800 rpm
Handle Type	Pistol

