

HIOKI 3030-10 | HiTESTER | Basic Analog Tester (20 kiloohm/V)



The Hioki 3030-10 is a rugged analogue multimeter that measures voltage, current, and resistance and can withstand a 1 metre drop onto concrete.

Specifications	Details
Part number	3030-10
Brand	Hioki
Power Supply	For resistance measurement range, R6P (AA) $\tilde{\square}$ 2 batteries
Resistance range	0 to 3 k $\hat{\text{I}}\text{C}$ (center scale 30 $\hat{\text{I}}\text{C}$), R $\tilde{\square}$ 1, R $\tilde{\square}$ 10, R $\tilde{\square}$ 100, R $\tilde{\square}$ 1 k Accuracy: $\hat{\text{A}}\pm 3$ % of scale length
AC Voltage range	12 V (9 k $\hat{\text{I}}\text{C}/\text{V}$) Accuracy: $\hat{\text{A}}\pm 4$ % f.s. 30/120/300/600 V (9 k $\hat{\text{I}}\text{C}/\text{V}$) Accuracy: $\hat{\text{A}}\pm 2.5$ % f.s. Average rectifier effective value, Max. rated voltage: 600 V
DC Voltage range	0.3 V (16.7 k $\hat{\text{I}}\text{C}/\text{V}$), 3/12/30/120/300/600 V (20 k $\hat{\text{I}}\text{C}/\text{V}$) Accuracy: $\hat{\text{A}}\pm 2.5$ % f.s. Max. rated voltage: 600 V

