

## York 125x22mm ALUM/BACK ZIRC FLAP DISC P60



Zirconium Grade Aluminium-Backed High performance alternative to sanding discs. Have the advantage over depressed centre grinding discs on light gauge sheet metal where surface finish is important. Overlapped abrasive strips slowly wear away revealing fresh abrasive, ensuring the disc always cuts effectively, reducing clogging, provides constant finish throughout disc life. No backing pads needed. Safe to use at 80m/s on any grinder. Tested at 150m/s and approved by the German Grinding Wheel Authority (DSA). Available in two grades and with two types of backing. 100mm Dia x 16mm Bore 15,300 MOS (rpm) 115mm Dia x 22mm Bore 13,300 MOS (rpm) 125mm Dia x 22mm Bore 12,000 MOS (rpm)

Specifications	Details
Features	Constant Finish, Cool and Fast Cutting with less Loading, Decreased Risk of Burning, High Stock Removal, Long life, Low Noise (Quieter than a grinding disc), Low Vibration, No Backing Pad Required, Reduces Disc Change down Time
Bore Diameter	22 mm
Maximum Operating Speed	12,000 rpm
Backing Material	Aluminium-Backed (General-purpose).
Grit	P60
Abrasive Material	Zirconium Oxide
Disc Diameter	125 mm
Product Number	5012386
Weight	1
Standards Met	Complies to oSa Regulations, Manufactured according to EN 13743
SKU	YRK2208230GTSK
Disc Type	Conical (Type 29)
Bore Thread Size	M14

Specifications	Details
Brand	York

