

Product information

Indicator gage Multimar 36B-10-VT

Product features

- Friction-free, zero-backlash measuring anvil holder for high measuring accuracy
- Parallel spring-loaded system for repeatable measuring force
- User-friendly and ergonomic:
 - Table surface can be tilted and clamped between 0° and 90°
 - Adjustable lifting of movable probe
- Adjustable measuring force

Application

- For measuring internal and external diameters, centering edges, narrow shoulders and recesses
- "T"-plates give a diameter reading directly across the diameter. A third contact may be used as a side-stop or centralizer
- "V"-plates are self-centralizing. Three jaws are used and the measurement is of the distance between the sensitive contact and the chord formed by the two reference contacts. This measurement bears a direct relationship to the diameter and compensation is made by a special ratio indicator so diameter is read directly. Used to inspect parts with odd number lobing conditions



Item no.: **2061657**

Technical data

Battery type	CR 2450N (3V Lithium)
Measuring force up to	35
Measuring force from	0
Mounting hole	8 mm
Application range, outside	6 - 127
Application range, inside	19 - 89
Resolution	0.0005 mm, 0.001 mm, 0.002 mm, 0.005 mm, 0.01 mm
Resolution	0.00002 inch, 0.00005 inch, 0.0001 inch, 0.0002 inch, 0.0005 inch

Accessories

Order no.	Designation	Product type
2225702	Measuring anvil for JW-9	PS-55