

Crane Scale HD

- High-visibility LED display (0.8inch)
- Lightweight & Robust enclosure
- Built in rechargeable battery and Low battery status lamp
- Key function : Power On/off, Zero, Tare, Hold
- Swivel hook (360° movement of working load)

OPTION > Double hook



Crane Scale NC-1

- Washdown aluminum case
- Wireless remote controller
- Battery operated with low battery indication
- Auto calibration and auto zero tracking
- On/off, zero, tare and hold function

< Double hook
(Option)



Remote Controller
Remote Controller provides easy & convenient operation from a distance.

LCD >



Crane Scale CASTON-I

- Washdown case
- Battery operated with low battery indication
- On/off, zero, tare and hold function
- Various display (LCD/LED)

Model	HD		NC-1				CASTON-I						
	100	200	500	50	100	200	500	0.1THA	0.2THA	0.3THA	0.5THA	1THA	2THA
Max.capacity (kg)	100	200	500	50	100	200	500	100	200	300	500	1,000	2,000
Readability (kg)	0.05	0.1	0.2	0.02	0.05	0.1	0.2	0.05	0.1	0.1	0.2	0.5	1
Resolution	1/2,000	1/2,500	1/2,500	1/2,000	1/2,000	1/2,500	1/2,000	1/2,000	1/3,000	1/2,500	1/2,500	1/2,000	1/2,000
Display digit	5 digits			5 digits				5 digits					
Display type	LED (10.8 inch)			LCD (1inch)				LCD (1inch) / LED (0.8inch)					
Operating temperature (°C)	-10 ~ +40			-10 ~ +40				-10 ~ +40					
Power	Rechargeable battery / DC Adapter			Rechargeable battery / DC Adapter				Rechargeable battery / DC Adapter					
Dimensions (mm) (W x D x H)	266 x 116 x 476			260 x 134 x 480				258 x 440 x 1,330					
Product weight (kg)	6.5			5.5				6.5	6.7		6.9		

Crane Scale CASTON (THZ)

- Easy-to-read
- 38mm LED display
- Aluminum die-casting enclosure
- High capacity rechargeable battery

OPTION > Extra Display > Stand Ass'y

Model	THZ-1A	THZ-2A	THZ-3A	THZ-5A	THZ-10A	THZ-20A
Max.capacity (kg)	1,000	2,000	3,000	5,000	10,000	20,000
Readability (kg)	0.5	1	1	2	5	10
External resolution	1/2,000	1/2,000	1/3,000	1/2,500	1/2,000	1/2,000
Keys	ON/OFF, ZERO, TARE, HOLD					
Function	Auto off set, Low voltage alarm, Resolution switch					
Display type	1.5 inch (38.1mm) ultra-luminance LED					
Operating temperature (°C)	-10 ~ +40					
Power	Rechargeable battery / DC Adapter					
Dimensions (mm) (W x D x H)	2ton: 230 x 350 x 420 / 5ton: 230 x 350 x 585 / 10ton: 230 x 350 x 770 / 20ton: 230 x 350 x 950					
Product weight (kg)	2 ton: 16 / 5ton: 25 / 10ton: 47, 20ton: 68					



Crane Scale CASTON-II

- Standard wireless remote controller
- Rechargeable battery pack
- Battery operated with low battery indication
- On/off, zero, tare and hold function
- Spare battery pack & charger included

OPTION > Bluetooth communication
> TWN (Portable handheld indicator)

Model	0.5THB	1THB	2THB	3THB	3THB (approval)	5THB
Max.capacity (kg)	500	1,000	2,000	3,000		5,000
Readability (kg)	0.2	0.5	1	2	1	2
Resolution	1/2,500	1/2,000	1/2,000	1/1,500	1/3,000	1/2,500
Display type	5 digits					
Operating temperature (°C)	LED (1.2inch)					
Power	-10 ~ +40					
Platter Size (mm)	Rechargeable battery / DC Adapter					
Dimensions (mm) (W x D x H)	258 x 440 x 380		230 x 370 x 474			230 x 370 x 518
Product weight (kg)	15	15	17		20	