


# VANE FLOW SWITCH

## Low Cost, Field Adjustable Set Point and Paddle



Shown with conduit connection option

The **Series FS-2 Vane Flow Switch** offers an economical flow proving solution. The FS-2 paddles are adjustable to fit 1 to 8" size pipe.

**BENEFITS/FEATURES**

- Field adjustable set point adjustment screw allows for easy flow switch modification
- Custom application set points enabled by field adjustable vane layers
- Aluminum weatherproof housing permits outdoor installation

**APPLICATIONS**

- Boiler flow proving
- Hot water heaters
- Chillers
- Cooling lines
- Machinery
- Liquid transfer systems

**SPECIFICATIONS**

**Service:** Compatible liquids.  
**Wetted Materials:** Bellow: Tin-bronze; Vane: SS; Body: Forged brass.  
**Temperature Limit:** 230°F (110°C).  
**Pressure Limit:** 145 psig (10 bar).  
**Enclosure Rating:** NEMA 4 (IP64).  
**Switch Type:** SPDT snap switch.  
**Electrical Rating:** 10 A res, 3 A ind @ 250 VAC.  
**Electrical Connection:** Cable gland with attached wire leads or optional conduit connection.  
**Process Connection:** 1" male NPT or BSPT.  
**Mounting Orientation:** Switch must be installed vertically on horizontal pipe runs.  
**Set Point Adjustment:** Four vane combinations and an adjustment screw.  
**Enclosure:** Die-cast aluminum alloy.  
**Weight:** 28.22 oz (0.8 kg).  
**Compliance:** CE.

APPROXIMATE ACTUATION/DEACTUATION FLOW RATES FOR WATER; GPM (LPM)					
Pipe Size	Blade Vane Length in (mm) Dim. X	Minimum Setting		Maximum Setting	
		Actuate	Deactuate	Actuate	Deactuate
1"	1.34 (34)	4.0 (15.0)	1.8 (6.7)	8.8 (33.3)	6.6 (25.0)
1-1/4"	1.34 (34)	5.3 (20.0)	2.6 (10.0)	11.4 (43.3)	8.4 (31.7)
1-1/2"	2.24 (57)	7.0 (26.7)	4.0 (15.0)	14.5 (55.0)	11.4 (43.3)
2"	2.24 (57)	14.1 (53.3)	9.7 (36.7)	31.3 (118.3)	22.5 (85.0)
2-1/2"	3.46 (88)	18.5 (70.0)	15.4 (58.3)	35.2 (133.3)	30.8 (116.7)
3"	3.46 (88)	27.7 (105.0)	25.1 (95.0)	52.8 (200.0)	46.2 (175.0)
4"	3.46 (88)	59.4 (225.0)	52.8 (200.0)	123.3 (466.7)	114.5 (433.3)
5"	6.57 (167)	52.8 (200.0)	39.6 (150.0)	132.1 (500.0)	123.3 (466.7)
6"	6.57 (167)	75.7 (286.7)	52.8 (200.0)	154.1 (583.3)	140.9 (533.3)
8"	6.57 (167)	184.9 (700.0)	158.5 (600.0)	396.3 (1500.0)	374.2 (1416.7)

MODEL CHART	
Model	Description
FS-2	Paddle flow switch

OPTIONS	
To order add suffix:	Description
-BSPT	Process connection
<b>Example:</b> FS-2-BSPT	
-CND	Conduit connection, 1" NPT female conduit connection with no wire leads
<b>Example:</b> FS-2-CND	

Flow Switches,  
Paddle

USA: California Proposition 65  
**WARNING:** This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).