


EVT008

ADOAH043VAS0010E04

Connection technology



Product characteristics

Socket

For sensors with

M12 connector

Free from silicone

Gold-plated contacts

–

For hygienic and wet areas in the food industry

Electrical data

Electrical design		DC PNP
Operating voltage	[V]	10...36 DC
Current rating	[A]	4
Protection class		II

Environment

Ambient temperature	[°C]	-25...100, cRUus: max. 50 °C
Ambient temperature (moving)	[°C]	5...100, cRUus: max. 50 °C
Protection		IP 65 / IP 67 / IP 68 / IP 69K

Tests / approvals

MTTF	[Years]	20027
------	---------	-------

Mechanical data

Design		angled
Material body		housing: PVC black transparent; sealing: EPDM
Material nut		stainless steel 316L / 1.4404
Tightening torque for knurled nut [Nm]		0.6...1.5
Weight	[kg]	0.362

Displays / operating elements

Output status indication	LED	2 x yellow
Operation	LED	green

Electrical connection

Connection		PVC cable / 10 m; 4 x 0.34 mm ² (42 x Ø 0.1 mm); Ø 4.9 mm
Sheath colour		orange



Wiring

EVT008

ADOAH043VAS0010E04

Connection technology

Core colours
BK black
BN brown
BU blue
WH white



Remarks

Pack quantity [piece] 1